


- 1 RHEINZINK - Roof Drainage
 - Gutter
- 2 RHEINZINK - Double Standing Seam - Roof
- 16 RHEINZINK - Building Profile
 - a Eaves flashing
 - c Perforated strip
 - q Cover flashing
 - r Render flashing
- 18 Support Profile
 - a Galvanised steel
- 19 Separating Layer
 - a Structured underlay VAPOZINC®
 - c Structured mat
- 20 Substructure
 - h OSB/ veneer plywood sheathing, thickness min. 18 mm
 - i Softwood boarding/ plywood 12 mm x 150 mm
- 21 Batten/ Squared Timber
 - Squared timber
- 22 Functional Layer
 - c Waterproof layer
- 23 Supporting Structure
- 30 Ventilated Air Space



STANDARD DETAIL

Box Gutter to a Parapet Wall + Safety waterproof layer + Structured mat	Title	Scale
		1:2
		Size
		A3
	Detail-Nr.	Drawn
	09020203010211000102_GB_en	WGM
		Date
		30.01.14

The detail describes an optional design in standard cases based on a European climate. Any user of this document is responsible to verify the feasibility of the solution with respect to the specific local situation and conditions. Using the documents provided by RHEINZINK is a service, which excludes liability for damages or claims of any kind. Contingent liability for malice or gross negligence is unaffected.